

## Technical Data Sheet

# B7170

Fabric / Weefsel / Tissu / Gewebe / Tejido	100 % PES / 1100 dtex	
Total weight / Gewicht totaal / Poids total / Totalgewicht / Peso total	520 g/m <sup>2</sup>	DIN EN ISO 2286/2 1998
Characteristics / Eigenschappen / Caractéristiques / Eigenschaften / Characteristics	ABUV/TRANSLUCENT	
Comment / Opmerking / Remarque / Kommentar / Comentario	SIOFLUO	
Lacquering / Vernis / Lackierung / Lacado	1/1	
Embossing / Kalander / Calandre / Lackierung / Embossing	Glossy	
Breaking strength Warp Treksterkte Ketting Résistance rupture Chaîne Höchstzugkraft Kette Resistencia a la ruptura Urdimbre	2500 N/5cm	EN ISO 1421/1 1998
Breaking strength Weft Treksterkte Inslag Résistance rupture Trame Höchstzugkraft Schuss Resistencia a la ruptura Trama	2000 N/5cm	EN ISO 1421/1 1998
Tear strength Warp Scheurweerstand Ketting Résistance à la déchirure Chaîne Weiterreisskraft Kette Resistencia a la rasgadura Urdimbre	250 N	DIN 53363 2003
Tear strength Weft Scheurweerstand Inslag Résistance à la déchirure Trame Weiterreisskraft Schuss Resistencia a la rasgadura Trama	200 N	DIN 53363 2003

"This product may for certain colours contain substances (Lead Pigments ) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.  
In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.  
Upon request those substances can be eliminated from the product."

Technical Data Sheet

## B7170

Adhesion / Hechting / Adhérence / Haftung / Adherencia	60 N/5cm	EN ISO 2411 2000
Temperature resistance / Temperatuursbestendigheid / Tenue à la température / Temperatuursbestendigheid / Resistencia à la temperatura	-30/+70 °C	DIN EN 1876/2 1998
Light transmission	40%	
Licht transmissie		
Transmission de la lumière		
Lichtdurchlässigkeit		
Light transmission		
Fire behavior / Brandgedrag / Reaction au feu / Brennverhalten / Fire behavior	M2	NF P 92 507 2004
Fire behavior / Brandgedrag / Réaction au feu / Brennverhalten / Fire behavior	B1	DIN 4102 1981
Application Tent&TA/sidewall/Plain		

"This product may for certain colours contain substances (Lead Pigments ) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.  
 In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.  
 Upon request those substances can be eliminated from the product."