

Technical Data Sheet

B7169

Fabric / Weefsel / Tissu / Gewebe / Tejido	100 % PES / 1100 dtex	
Total weight / Gewicht totaal / Poids total / Totalgewicht / Peso total	650 g/m ²	DIN EN ISO 2286/2 1998
Characteristics / Eigenschappen / Caractéristiques / Eigenschaften / Characteristics	ABUV	
Lacquering / Vernis / Lackierung / Lacado	1/1	
Embossing / Kalander / Calandre / Lackierung / Embossing	Glossy	
Breaking strength Warp Treksterkte Ketting Résistance rupture Chaîne Höchstzugkraft Kette Resistencia a la ruptura Urdimbre	2500 N/5cm	EN ISO 1421/1 1998
Breaking strength Weft Treksterkte Inslag Résistance rupture Trame Höchstzugkraft Schuss Resistencia a la ruptura Trama	1800 N/5cm	EN ISO 1421/1 1998
Tear strength Warp Scheurweerstand Ketting Résistance à la déchirure Chaîne Weiterreisskraft Kette Resistencia a la rasgadura Urdimbre	250 N	DIN 53363 2003
Tear strength Weft Scheurweerstand Inslag Résistance à la déchirure Trame Weiterreisskraft Schuss Resistencia a la rasgadura Trama	200 N	DIN 53363 2003
Adhesion / Hechting / Adhérence / Haftung / Adherencia	100 N/5cm	EN ISO 2411 2000

"This product may for certain colours contain substances (Lead Pigments) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.
In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.
Upon request those substances can be eliminated from the product."

Technical Data Sheet

B7169

Light fastness (Except white and (half-)transparent)	7-8	ISO 105 B02 1988
Lichtechtheid (Uitgezonderd wit en (half-)transparent)		
Tenue à la lumière (Excepté en blanc et (semi-)transparent)		
Lichtechtheit (Ausnahme weiss und (semi-)transparent)		
Resistencia a la luz (Excepto blanco / (semi-)transparente)		
Temperature resistance / Temperatuursbestendigheid / Tenue à la température / Temperatursbeständigkeit / Résistencia à la temperatura	-30/+70 °C	DIN EN 1876/2 1998
Fire behavior / Brandgedrag / Reaction au feu / Brennverhalten / Fire behavior	M2	NF P 92 507 2004
Reaction to fire / Reactie bij brand / Reaction au feu / Brennverhalten / Reacción al fuego	B-s2,d0	EN 13501-1 2007
Application Tent&TA/Sidewall/Plain		

"This product may for certain colours contain substances (Lead Pigments) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.
 In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.
 Upon request those substances can be eliminated from the product."