

Technical Data Sheet

B9224

Fabric / Weefsel / Gewebe / Tejido / Tissu	100 % PES / 1100 dtex	
Total weight / Gewicht totaal / Totalgewicht / Peso total / Poids total	1150 g/m ²	DIN EN ISO 2286/2 1998
Characteristics / Eigenschappen / Eigenschaften / Characteristics / Caractéristiques	AB	
Lacquering / Vernis / Lackierung / Lacado / Vernis	1/1	
Embossing / Kalander / Lackierung / Embossing / Calandre	Glossy	
Breaking strength Warp Treksterkte Ketting Höchstzugkraft Kette Resistencia a la ruptura Urdimbre Résistance rupture Chaîne	2700 N/5cm	DIN EN ISO 13934-1
Breaking strength Weft Treksterkte Inslag Höchstzugkraft Schuss Resistencia a la ruptura Trama Résistance rupture Trame	2700 N/5cm	DIN EN ISO 13934-1
Tear strength Warp Scheurweerstand Ketting Weiterreisskraft Kette Resistencia a la rasgadura Urdimbre Résistance à la déchirure Chaîne	150 N	DIN 53356 / A
Tear strength Weft Scheurweerstand Inslag Weiterreisskraft Schuss Resistencia a la rasgadura Trama Résistance à la déchirure Trame	150 N	DIN 53356 / A
Adhesion / Hechting / Haftung / Adherencia / Adhérence	125 N/5cm	EN ISO 2411 2000

"This product may for certain colours contain substances (Lead Pigments) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.
In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.
Upon request those substances can be eliminated from the product."

Technical Data Sheet

B9224

Water absorption (If combined with non woven)	> 600 g/m ²	DIN 53923
Water absorptie (Indien met non woven gecombineerd)		
Wasseraufsaugung (Wenn es mit nichtgewebtem Stoff kombiniert wird)		
Water absorption (If combined with non woven)		
Absorption d'eau (En combinaison avec non woven)		
Temperature resistance / Temperatuursbestendigheid / Temperatursbeständigkeit / Résistencia à la temperatura / Tenue à la température	-30/+85 °C	DIN EN 1876/2 1998
Light fastness (Except white and (half-)transparent)	6	ISO 105 B02 1988
Lichtechtheid (Uitgezonderd wit en (half-)transparent)		
Lichtechtheit (Ausnahme weiss und (semi-)transparant)		
Resistencia a la luz (Excepto blanco / (semi-)transparente)		
Tenue à la lumière (Excepté en blanc et (semi-)transparent)		
Fire behavior / Brandgedrag / Brennverhalten / Fire behavior / Réaction au feu	B1	DIN 4102 1981
Application Railway/Tilt/Anti-Cond		
TD Haubendach-Planen rev.07/2009	Conform	

"This product may for certain colours contain substances (Lead Pigments) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.
In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.
Upon request those substances can be eliminated from the product."